



UNIFILTER FUEL OIL FILTERS



77B and 99B Fuel Oil Filters

Compatible with Fuel Oil Conforming to ASTM D396-09 (up to B5)!

- Working pressure = 40 PSI. ETL Listed. 3/8" NPT standard
- Now with durable epoxy coated galvanized steel filter bowl Inside & out
- **4EVERLoc** bottom bolt design



RF-1 and RF-2


micRoFiber RF Filter Element Cartridge Standard with 77B & 99B

77B Oil Filter 99B Oil Filter


Compatible with Bio-Fuel Blends up thru B5!

- Durable epoxy coated galvanized steel bowl inside & out
- **4EVERLoc** Bottom Bolt Design

Clean Pressure Drop No. 2 Fuel Oil 77B



Clean Pressure Drop No. 2 Fuel Oil 99B



9300

77B 3/8" Unifilter Fuel Oil Filter
10 GPH Firing Rate at 10 Microns 40 PSI



9302

99B 3/8" Unifilter Fuel Oil Filter
25 GPH Firing Rate at 10 Microns 40 PSI

SPECIFICATIONS

	77B	99B
Height	5-1/8 in.	6-1/4 in.
Diameter	3-5/8 in.	4-3/8 in.
Weight	2 lbs.	3 lbs.
Pipe Size	3/8" N.P.T. STD.	3/8" N.P.T. STD.
Working Pressure	40 P.S.I.	40 P.S.I.
Firing Rate-#2 Fuel Oil	10 GPH	25GPH
Replacement Elements	Pt. No. RF-1	Pt. No. RF-2
Filter Media	micRoFiber (10 Micron)	micRoFiber (10 Micron)
micRoFiber RF Surface	52 Square Inches	90 Square Inches
micRoFiber RF Volume	12 Cubic Inches	22.7 Cubic Inches

Unifilter 77B & 99B Oil Filter Specifications